

Technical drawing of the EzI-SERVO PR-28M, showing three views: front, side, and isometric.

Front View Dimensions:

- Overall length: 173
- Distance from front face to servo motor: 66,6
- Distance from front face to first hole: 8,6
- Distance between holes: 40, 40, 40
- Distance from last hole to servo motor: 46
- Overall width: 30
- Distance from top/bottom face to hole center: 23,5
- Mounting holes: $\phi 3,4, \phi 5,5$
- Base width: 130

Side View Dimensions:

- Overall height: 33,5
- Distance from top face to hole center: 30
- Distance from bottom face to hole center: 8,6
- Distance from front face to hole center: 40
- Distance from front face to servo motor: 50
- Distance from front face to servo motor: 13


Isometric View Dimensions:

- Overall length: 50
- Distance from front face to first hole: 20
- Distance between holes: 20, 20
- Distance from last hole to servo motor: 10, 10
- Distance from front face to servo motor: 3
- Mounting holes: 12x M3 $\nabla 5,5$

Labels:

- EzI-SERVO PR-28M
- 12x M3 $\nabla 5,5$
- $\phi 3,4, \phi 5,5$

Table:

Gewicht		ISO 5456		Dokumentenstatus		Format	
0,000 kg				Entwurf		A3	
GMT Europe GmbH Wilhelm-Busch-Str. 4 26655 Westerstede Deutschland Phone: +49 (0) 4488 761746-0 E-Mail: info@gmteurope.de © Copyright 2022 GMT Europe. Alle Rechte vorbehalten.		 GMT Europe GmbH		Ersteller		pok	
				Genehmiger		mm	
				Ausgabedatum		24.08.2022	
Typ		Abteilung		Artikelnummer		Revision	
CXN5050-P2-Ezi-Servo-PR-28M		R&D					

